

**GCFS**

*Constant Force Spring*

**Features**

- ⊙ Easily applied by rolling onto the sheath connections
- ⊙ Exert a constant pressure whereupon
- ⊙ Nonmagnetic
- ⊙ Same spec. and performance to Raychem's EPPA-034 series

Components



**Dimensions**

Part NO.	Application range/mm		Dimensions/mm			
	Min.	Max.	Inner dia.	Width	Thickness	Length
GCFS-A	12	20	10	13	0.15	280
GCFS-K	12	20	10	13	0.15	400
GCFS-B	17	28	14	13	0.18	400
GCFS-C	25	40	20	13	0.2	570
GCFS-D	36	60	30	13	0.26	850
GCFS-E	17	29	14	25	0.2	570
GCFS-F	30	39	22	25	0.3	700
GCFS-G	40	60	30	25	0.35	950
GCFS-H	50	75	38	30	0.4	1100
GCFS-I	50	75	38	30	0.4	1350
GCFS-L	57	85	45	30	0.4	1350
GCFS-M	23	45	25	25	0.33	800
GCFS-N	25	34	25	20	0.25	650
GCFS-O	85	110	70	30	0.4	1500
GCFS-U	110	135	70	30	0.65	1700

Special sizes available upon request

GCFS of constant force spring made from fatigue Resistant Stainless Steel which had been heat-treated and coiled.

Typical used for solderless shield and armour Connections, Securing grade brades when splicing and terminating power cable.

**Ordering information**

Color	Standard	Gold
Ordering description	Nonstandard	Silver
	Specify product name and type (for example, GCFS-L)	

\* Other sizes are available on request.