

Cold Shrink Parts

GCMB

Cold Shrink 3 cores cable Breakout


Features

- ⊙ Quick, easy and safe installation
- ⊙ Immediate reenergizing
- ⊙ High mechanical strength
- ⊙ Waterproof
- ⊙ Accommodates a wide range of cable sizes
- ⊙ Retains its resiliency and pressure



Key technical performances

| Test Items | Test Method | Test Requirements |
|---------------------|-------------|----------------------|
| Tensile strength | ASTM D 638 | 7MPa min. |
| Ultimate elongation | ASTM D 638 | 600% min. |
| Tear strength | ASTM D 638 | 20KN/m min. |
| Density | ASTM D 792 | 1.2g/cm ³ |



Selection table

| Size(mm) | D(mm) | | l(mm) | | Recovered wall (±20%) l _w | Recovered length (±10%) | |
|-------------|-----------|-----------|-----------|-----------|---|-------------------------|----|
| | a* (Min.) | b* (Max.) | a* (Min.) | b* (Max.) | | L | F |
| GCMB-75/38 | 75 | 38 | 31 | 14 | 2.5 | 170 | 45 |
| GCMB-92/43 | 92 | 43 | 36 | 16 | 2.5 | 180 | 45 |
| GCMB-105/53 | 105 | 53 | 41 | 19 | 2.5 | 190 | 45 |
| GCMB-120/62 | 120 | 62 | 48 | 23 | 3.5 | 201 | 45 |
| GCMB-160/68 | 160 | 68 | 67 | 27 | 3.5 | 230 | 60 |
| GCMB-200/85 | 200 | 85 | 80 | 32 | 3.5 | 230 | 60 |

*NOTE:
a* = Inner diameter as supplied
b* = Inner diameter after fully recovered

Ordering information

| Color | Standard | Grey |
|----------------------|---|------|
| Ordering description | Specify product name, size(for example, GCMB-92/43) | |

ELECTRIC POWER

Cold Shrink Parts / GCST / GCMB